


**Welded flange ring,
stainless steel
304/1.4301, DN 250 ISO-
K**




Welding flange ring



Welded flange ring, stainless steel 304/1.4301, DN 250 ISO-K

Dimensions



A	290 mm
B	261 mm
C	12 mm
§D §D	254.4 mm
§E §E	7 mm

Technical Data	Welded flange ring, stainless steel 304/1.4301, DN 250 ISO-K
Temperature range min.	-196 °C
Temperature range max.	300 °C
Materials in contact with media	Stainless steel 1.4301 (AISI 304)
Pipe dimension	254 mm × 2 mm
Temperature range	-196 – 300 °C
Connection flange	DN 250 ISO-K
Pressure range	1E-8 hPa – 1.5E3 hPa over pressure (elastomer seal); 1E-9 hPa – 1.5E3 hPa over pressure (metal s · 10al)
Temperature range max.	300 °C 572 °F 573.15 K
Temperature range min.	-196 °C -320.8 °F 77.15 K

Order number	Welded flange ring, stainless steel 304/1.4301, DN 250 ISO-K
Welded flange ring, stainless steel 304/1.4301, DN 250 ISO-K	320FAN250-254

Your Success. Our Passion.

We give our best for you every day –
worldwide!

Are you looking for an optimum vacuum solution?

Talk to us:

Pfeiffer Vacuum Components & Solutions GmbH Germany

T +49 551 99963-0

info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 11/1/2024

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER  **VACUUM**