




**CCT 362, tube OD 1/2",  
RS-485**



## CCT 362, tube OD ½", RS-485

- Measurement range:  $1 \cdot 10^{-2}$  – 110 hPa
- Pressure measurement independent of type of gas
- Minimal zero drift
- Precise temperature compensation
- Sensor in ceramic technology
- Calibration test report included in delivery

## Dimensions



<b>Technical Data</b>	<b>CCT 362, tube OD ½", RS-485</b>
Measuring range	1E-2 – 1.1 · 10 <sup>2</sup> hPa
Materials in contact with media	Ceramic (Al <sub>2</sub> O <sub>3</sub> = 99.5 %)   Stainless steel (AISI 316L)
Measurement cable length	100 m
Temperature effect: on zero point	0,005 % F.S./°C
Temperature effect: on range	0.01% of measured value/ °C
I/O interfaces	RS-485
Anode	130727
Ambient temperature	5 – 50 °C
Measuring method	Capacitive
Input voltage(s)	14 – 30 V DC
Bakeout temperature at the flange	≤110 °C   ≤230 °F   ≤383.15 K
Pressure max.	2,600 hPa   1,950 Torr   2,600 mbar
Full scale	100 hPa   75 Torr   100 mbar
Weight	0.62 kg   1.37 lb
Resolution	0.003 % F.S.
Measuring cycle	60 ms
Power consumption max.	2 W
Connection flange	Rohr AD ½"
Electrical connection	RS485, M12, 5-pole, socket, a-coded
Accuracy of measurement	0.2 % (of measured value)

<b>Order number</b>	<b>CCT 362, tube OD ½", RS-485</b>
CCT 362, tube OD ½", RS-485	PT R51 060

## Your Success. Our Passion.

We give our best for you every day –  
worldwide!

Are you looking for an optimum vacuum solution?

Talk to us:  
Pfeiffer Vacuum GmbH  
Germany  
T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 11/15/2024

Follow Us On Social Media  
#pfeiffervacuum



[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

**PFEIFFER**  **VACUUM**